


Black Circles = Printable Area
Red Circle = Outer Edge of Mirror Band



Docket #: 3454
Job name: Sample Disc
Date: January 23, 2006
Disc Type: Full Size CD
Colors: CMYK on white
100 LPI

IMPORTANT: Artwork issues are the largest single cause of manufacturing delays. Artwork that is not supplied to our specifications may be rejected, which may result in the delay of your order. For complete guidelines and specifications please contact your Sales Representative.

- Most good graphic design programs will allow you to design in 'layers'. This template is designed as a 'mask' that occupies one layer.
- You must place your artwork underneath our template/mask layer. When you do so the mask will reveal the portions of the design that will print on the disc face.
- Do not trim your artwork to fit the outside edges of the allowable print area (let your design 'bleed' past the edge).
- Do not create your own center hole in your design (the template will mask that area automatically).
- The dotted red line on the template represents the outside edge of the mirror band. If you are using the disc's silver surface colour as a part of your design, only reveal the disc surface OUTSIDE of the mirror band (the area inside the mirror band is mostly clear plastic).

GENERAL DESIGN RULES:

- Artwork files are to be in final form (ready to print without changes or revisions).
- Supply a colour printout (or .PDF file) of your finished artwork as a 'proof' for us to check your artwork files against.
- It is preferred that final artwork files are supplied in .EPS file format, however, supplying your native artwork file is also helpful.
- The template/mask must remain on a separate removable layer. Do not 'flatten' your design with the template in it.
- Set your design page properties to CMYK (not RGB).
- All scanned or bitmap images are to be 300 dpi and in the CMYK or Greyscale colour mode (saved in .TIF or .TIFF format).
- Place or link your images (do not embed them) and include a copy of all image files used.
- Minimum text size: 4 points OR 6 points if reverse.
- Minimum line width: 0.15mm (½ point) OR 0.30mm (1 point) if reverse.
- All text must be converted to curves/outlines or you must supply all font files used in the design.
- Acceptable tonal range for screens or gradients is between 15% and 85%. Tones outside that range won't print.
- You must indicate whether you require a white flood/backprint.

IF YOUR DISC ARTWORK IS BEING SCREENPRINTED USING PANTONE/SPOT COLOURS:

- Do not design using transparencies or drop shadows. Use solid colours whenever possible and only use screens/gradients when necessary.
- Screenprinting prints one colour on each screen (to a maximum of six). Your design must be colour-separable.
- Minimum trapping is 0.5 point or 0.18 mm
- If you are not designing for CMYK Process Printing, you must specify Pantone Matching System (PMS) colour numbers.